

## 2015 Challenger Specifications

Feature	Model	
	<b>2752BSJ-510</b>	<b>2760BSJ-510</b>
Product Name	2752BSJ-510	2760BSJ-510
Engine	Briggs & Stratton Commercial Turf	Briggs & Stratton Commercial Turf
Horsepower	27	27
Cylinders	2	2
Oil Capacity	2.1 qt (2 L)	2.1 qt (2 L)
Drive System	HydroGear ZT-3400	HydroGear ZT-3400
Fuel Capacity	7 Gallon	7 Gallon
Steering Control	Joystick	Joystick
Stand-up Deck	Standard	Standard
Pivoting Front Axle	Standard	Standard
Roll Over Protection- Folding (ROPS)	Optional	Optional
Tires, Rear	22x11-10	22x11-10
Tires, Front	13x6.5-6	13x6.5-6
Turning Radius	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	9 mph/5 mph	9 mph/5 mph
Length	79"	79"
Height : top of seat back	46"	46"
Width, Tractor (outside rear tires)	49"	49"
Width, Deck w/ Chute	65"	73"
Width, Deck Chute Up	53"	61"
Cutting Width	52"	60"
Cutting Height	1.5" - 5" (1/4" increments)	
Deck Construction	Laminated Welded 12 Gauge Steel Deck with 10 Gauge Strategic Reinforcements, including protective bullnose front & high impact anti-scalp rollers; 3/8" x 2" wear bar on trim edge	
Deck Engagement	Electric, Warner®	
Blade Length	18-3/8"	21"
Spindle Assembly	Cast iron housing; 1.4" diameter shaft; maintenance free & field serviceable	
Blade Tip Speed, approx.	19,000 fpm	19,000 fpm
Weight	895 lbs	906 lbs
Seat	High Back, Enhanced Comfort Seat with Adjustable Slides	
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step	

Due to continuous product improvement, specifications are subject to change without notice.

## 2015 Challenger Specifications

Feature	Model			
Product Name	<b>2452KAJ-510</b>	<b>2460KAJ-510</b>	<b>2552KOJ-510</b>	<b>2560KOJ-510</b>
Engine	Kawasaki FS730	Kawasaki FS730	Kohler ZT740	Kohler ZT740
Horsepower	24	24	25	25
Cylinders	2	2	2	2
Oil Capacity	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2 qt (1.9 L)	2 qt (1.9 L)
Drive System	HydroGear ZT-3400	HydroGear ZT-3400	HydroGear ZT-3400	HydroGear ZT-3400
Fuel Capacity	7 Gallon	7 Gallon	7 Gallon	7 Gallon
Steering Control	Joystick	Joystick	Joystick	Joystick
Stand-up Deck	Standard	Standard	Standard	Standard
Pivoting Front Axle	Standard	Standard	Standard	Standard
Roll Over Protection- Folding (ROPS)	Optional	Optional	Optional	Optional
Tires, Rear	22x11-10	22x11-10	22x11-10	22x11-10
Tires, Front	13x6.5-6	13x6.5-6	13x6.5-6	13x6.5-6
Turning Radius	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph
Length	79"	79"	79"	79"
Height : top of seat back	49"	49"	49"	49"
Width, Tractor (outside rear tires)	49"	49"	49"	49"
Width, Deck w/ Chute	65"	73"	65"	73"
Width, Deck Chute Up	53"	61"	53"	61"
Cutting Width	52"	60"	52"	60"
Cutting Height	1.5" - 5" (1/4" increments)			
Deck Construction	Laminated Welded 12 Gauge Steel Deck with 10 Gauge Strategic Reinforcements, including protective bullnose front & high impact anti-scalp rollers; 3/8" x 2" wear bar on trim edge			
Deck Engagement	Electric, Warner®			
Blade Length	18-3/8"	21"	18-3/8"	21"
Spindle Assembly	Cast iron housing; 1.4" diameter shaft; maintenance free & field serviceable			
Blade Tip Speed, approx.	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm
Weight	895 lbs	906 lbs	895 lbs	906 lbs
Seat	Deluxe cushioned embossed seat with static suspension and adjustable slides			
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step			

Due to continuous product improvement, specifications are subject to change without notice.