

2015 Edge XLT Specifications

Feature	Model				
	2448KAJ-455	2452KAJ-455	2452KAT-455	2460KAJ-455	2460KAT-455
Product Name	Kawasaki FR730	Kawasaki FR730	Kawasaki FR730	Kawasaki FR730	Kawasaki FR730
Engine	Kawasaki FR730	Kawasaki FR730	Kawasaki FR730	Kawasaki FR730	Kawasaki FR730
Horsepower	24	24	24	24	24
Cylinders	2	2	2	2	2
Oil Capacity	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)
Drive System	HydroGear ZT-2800	HydroGear ZT-2800	HydroGear ZT-2800	HydroGear ZT-2800	HydroGear ZT-2800
Fuel Capacity	5 Gallon	5 Gallon	5 Gallon	5 Gallon	5 Gallon
Steering Control	Joystick	Joystick	Twin Lever	Joystick	Twin Lever
Stand-up Deck	Standard	Standard	Standard	Standard	Standard
Pivoting Front Axle	Standard	Standard	Standard	Standard	Standard
Tires, Rear	20x10-10	20x12-10	20x12-10	20x12-10	20x12-10
Tires, Front	13x5-6	13x5-6	13x5-6	13x5-6	13x5-6
Turning Radius	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
Length	78"	78"	78"	78"	78"
Height : top of seat back	45"	45"	45"	45"	45"
Width, Tractor (outside rear tires)	49"	49"	49"	49"	49"
Width, Deck w/ Chute	61"	65"	65"	73"	73"
Width, Deck Chute Up	49"	53"	53"	61"	61"
Cutting Width	48"	52"	52"	60"	60"
Cutting Height	1" - 4" (1/2" Increments)				
Deck Construction	Laminated Welded 14 Gauge Steel Deck with 10 Gauge Strategic Reinforcements, including protective bullnose front & high impact anti-scalp rollers				
Deck Engagement	Electric, Warner®				
Blade Length	17"	18-3/8"	18-3/8"	21"	21"
Spindle Assembly	Cast iron housing; 1.4" diameter shaft; maintenance free & field serviceable				
Blade Tip Speed, approx.	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm
Weight	818 lbs	822 lbs	822 lbs	853 lbs	853 lbs
Seat	High Back, Enhanced Comfort Seat with Adjustable Slides				
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step				

Due to continuous product improvement, specifications are subject to change without notice.

2015 Edge XLT Specifications

Feature	Model				
	2648KOJ-455	2652KOJ-455	2652KOT-455	2660KOJ-455	2660KOT-455
Product Name	2648KOJ-455	2652KOJ-455	2652KOT-455	2660KOJ-455	2660KOT-455
Engine	Kohler KT745				
Horsepower	26				
Cylinders	2				
Oil Capacity	2.0 qt (1.9 L)				
Drive System	HydroGear ZT-2800				
Fuel Capacity	5 Gallon				
Steering Control	Joystick		Twin Lever		Joystick
Stand-up Deck	Standard				
Pivoting Front Axle	Standard				
Tires, Rear	20x10-10		20x12-10		20x12-10
Tires, Front	13x5-6				
Turning Radius	Zero-Turn				
Ground Speed (Forward/Reverse)	8 mph/4 mph				
Length	78"				
Height : top of seat back	45"				
Width, Tractor (outside rear tires)	49"				
Width, Deck w/ Chute	61"		65"		73"
Width, Deck Chute Up	49"		53"		61"
Cutting Width	48"		52"		60"
Cutting Height	1" - 4" (1/2" Increments)				
Deck Construction	Laminated Welded 14 Gauge Steel Deck with 10 Gauge Strategic Reinforcements, including protective bullnose front & high impact anti-scalp rollers				
Deck Engagement	Electric, Warner®				
Blade Length	17"		18-3/8"		21"
Spindle Assembly	Cast iron housing; 1.4" diameter shaft; maintenance free & field serviceable				
Blade Tip Speed, approx.	19,000 fpm				
Weight	818 lbs		822 lbs		853 lbs
Seat	High Back, Enhanced Comfort Seat with Adjustable Slides				
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step				

Due to continuous product improvement, specifications are subject to change without notice.